

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
26 May 2005 (26.05.2005)

PCT

(10) International Publication Number  
**WO 2005/046839 A1**

(51) International Patent Classification<sup>7</sup>: **B01D 33/50**

(21) International Application Number:  
PCT/SE2003/001746

(22) International Filing Date:  
12 November 2003 (12.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **NORDIC WATER PRODUCTS AB** [SE/SE]; Sisjö Kullegata 6, S-421 32 Västra Frölunda (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **LARSSON, Hans** [SE/SE]; Nordanvägen 68, S-137 38 Västerhaninge (SE).

(74) Agent: **HAGSTRÖM, Leif et al**; Bergenstrahle & Lindvall AB, P O Box 17704, S-118 93 Stockholm (SE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: APPARATUS FOR SEPARATING SUSPENSIONS



(57) Abstract: An apparatus for separating a suspension into a fine fraction and a coarse fraction of the suspension containing solid particles, comprises a rotatable filter disc (5) having a wall (6) of filtering material. During rotation of the filter disc the fine fraction passes through the wall of filtering material, while a mat of the coarse fraction of the suspension is deposited on the wall of filtering material. A mat detachment device (13) includes liquid jet nozzles (14) adapted to spray liquid jets that detach the mat of coarse fraction. The detachment device also includes air jet nozzles (15) adapted to spray air jets against the wall of filter material, so that the air jets participate in the detachment of the mat of coarse fraction and reduce the liquid dilution of the detached mat of coarse fraction.



---

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*